



ARS / ACS

ARSV / ACSV



ARS-210-3



LED



ARS-210-6

CARACTERÍSTICAS TÉCNICAS	TECHNICAL DATA	CARACTÉRISTIQUES TECHNIQUES
<ul style="list-style-type: none"> ARS refrigeración ACS congelación ARSV puerta cristal refrigeración ACSV puerta cristal congelación ARSP departamento pescado ARSM departamento congelados 	<ul style="list-style-type: none"> ARS cooling ACS freezing ARSV cooling double glazed doors ACSV freezing double glazed doors ARSP fish department ARSM frozen department 	<ul style="list-style-type: none"> ARS refroidissement ACS congélation ARSV refroidissement double vitrage ACSV congélation double vitrage ARSP département de poisson ARSM département gelé

Ver características técnicas en página 290 / See technical data in page 290 / Voir caractéristiques techniques page 290

* Gas opcional / * Optional gas / * Gaz optionnel

Modelo	Largo	Alto	Fondo	Rango	Estantes	Cajones	Pares de guías	Capacidad	Voltaje	Refrig.	Potencia Frig.	Consumo Nominal	Rango	clase climate
Model	Length	Height	Depth	Range	Shelves	Drawers	Sets of slides	Capacity	Voltage	Coolant	Frig Power	Nominal Consumption	Range	2015/1094 EN16825
Modèle	Longueur	Hauteur	Profondeur	Gamme	Étagères	Tiroirs	Kit de guides	Exposition	Tension	Frigorigène	Puissance Frig.	Consommation Nominale	Gamme	EN16825
ARS-210	2055	2160	735	-2°C / +8°C	9 + 6	0	0	1852	230 V - 50 Hz	R-290	1702	897	E	5 (40°C 40%)
ACS-210	2055	2160	735	-20°C / -15°C	9 + 6	0	0	1852	230 V - 50 Hz	R-290	1814	1680	E	4 (30°C 55%)
ARSV-210	2055	2160	735	-2°C / +8°C	12 + 8	0	0	1852	230 V - 50 Hz	R-290	1702	943	-	4 (30°C 55%)
ACSV-210	2055	2160	735	-20°C / -15°C	12 + 8	0	0	1852	230 V - 50 Hz	R-290	1814	1726	-	4 (30°C 55%)
ARSP-210	2055	2160	735	-2°C / +8°C / -5°C / -1°C	6 + 3	6	6	1725	230 V - 50 Hz	R-290 +R-290	845 + 845	370 + 431	-	-
ARSM-210	2055	2115	735	-2°C / +8°C / -20°C / -15°C	9 + 3	0	0	1725	230 V - 50 Hz	R-290 +R-290	845 + 361	370 + 642	-	-

PVP de opcionales incluidos en equipo, no como repuesto / PVP of options included in the equipment, not as a spare part / PVP d'options incluses dans l'équipement, pas en tant que pièce de rechange

OPCIONES - OPTIONS - OPTIONS			
Parrilla adicional 560 X 542	560 X 542 Extra shelf	Grille additionnelle 560 X 542	
Parrilla intermedia adicional 450 X 158	450 X 158 Extra middle shelf	Kit supplémentaire de guides 450 X 158	
Cerradura puerta inox	Solid door lock	Serrure à porte inox	
Cerradura puerta cristal	Glass door lock	Serrure à porte de verre	
Barras carniceras	Bars for meat set	Tube de boucher	
Set 6 ruedas	6 Castors set	Jeu 6 roulettes	
Set adicional guías	Slides extra set	Kit supplémentaire de guides	
Registrador de alarmas HACCP	HACCP alarm recorder	Enregistreur d'alarme HACCP	consultar - consult - consulter
Respaldo inox	Stainless steel rear side	Soutien en inox	consultar - consult - consulter
Tropicalizado 43°C	Tropicalized to 43°C	Tropicalisé 43°C	consultar - consult - consulter
230V 60hz / 115v 60hz	230V 60hz / 115v 60hz	230V 60hz / 115v 60hz	consultar - consult - consulter

Características técnicas y constructivas sujetas a variación sin previo aviso. / We reserve the right to change specifications without prior notice. / Sujet technique et la conception de modifications sans préavis.

